

**VALVES****FULL PORT BALL VALVE**

Size : ½" to 18"

Body Type : Two Piece, Three Piece, Floating, Trunnion Mounted/Jacketed

Rating : ANSI 150-900 CLASS

End Connections : Flange End, Butt Weld, Socket Weld

Face to Face : ASME B 16 10/API 6 D/ ISO 5752 SERIES 3/4/12

Body Materials : WCB/WCC/WC9, CF8M/CF3M, Hastelloy, Monel & other alloy

Bonnet : Standard, Extended bonnet available

Gland Packing : PTFE, Grafoil, Fugitive Emission Vacuum

Ball : Full Port, Reduced Port

Trim Material : SS304, SS316, Stellite-6, Alloy 20 and others

Shaft : 17-4PH

Gasket : Spiral Grafoil

Characteristics : On-Off

Seat Leakage : AS per FCI-70-2, Class IV, V & VI

Actuator Type : Rack & Pinion, Rotary Diaphragm Rotary Piston(Scotch Yoke)

Handwheel : MOR

Accessories : Pneumatic /Electro-Pneumatic/Smart/ Positioner, Air Set/Air Lock/ Volume Booster/ Solenoid Valve/ Limit Switch/Position Transmitter

Above Specifications are subject to change without notice