

GLOBE VALVE AUTOMATION



Size : 1/2" to 16"

Body Type : 2-way, 3-way

Rating : ANSI 150-2500 CLASS

End Connections : Flange End, Screwed,
Butt Weld, Socket Weld

Face to Face : ISA S.75.03 upto 600 class/
ISA S.75.16 upto 900 class

Body Materials : WCB/WCC/ WC9, CF8M/CF3M,
Hastelloy, Monel & other alloy

Bonnet : Standard, Extended bonnet available

Gland Packing : PTFE, Grafoil, Fugitive Emission"
Vacuum

Trim : Top Guided Contoured

Trim Material : SS3014, SS316, Stelite-6,
Alloy 20 and others

Gasket : Spiral Grafoil

Characteristics : Linear/ Equal Percentage/
Quick Opening

Seat Leakage : As per FCI-70-2, Class IV, V & VI

Actuator Type : Diaphragm, Piston, Electric

Actuator Action : Direct/ Reverse/ Double Acting

Handwheel : Top Mounted/ Side Mounted

Accessories : Pneumatic / Electro-Pneumatic/ Smart
Positioner, Air Set/Air Lock/ Volume Booster/ Solenoid
Valve/ Limit Switch/Position Transmitter

Above Specifications are subject to change without notice